

see over for more

# NEW from **BAL**

## levellers to cover every base

**To level any floor, BAL has the answer.**



**Five levellers all offering fantastic flow, brilliant bonding, virtually no shrinkage, great self-healing.**

	solidbase	rapidbase	thickbase	fibrebase	acrybase
Minimum bed depth	2mm	Feather edge	2mm	3mm	Feather edge
Maximum bed depth	12mm	15mm	50mm	30mm	10mm (20mm with chippings)
Time to foot traffic	4 hours	90mins	3-4 hours	3 hours	3 hours
Time to accept ceramic tiles	4 hours	2-3 hours	3-4 hours	4 hours	4 hours
Mix ratio	5:1	5:1	6:1	5:1	23.5kg powder : 5 litre liquid
Coverage mm/m <sup>2</sup>	1.6-1.7kg	1.6kg	1.7kg	1.6kg	1.9kg
Flow time	>15mins	>15mins	>15mins	>15mins	>15mins
Pack size	20kg	20kg	20kg	20kg	23.5kg powder : 5 litre liquid
Built in Polymer	Yes	Yes	Yes	Yes	No
Protein free	Yes	Yes	Yes	Yes	Yes
<b>Suitable surfaces:</b>					
Concrete	✓	✓	✓	✓	✓
Cement:sand screed	✓	✓	✓	✓	✓
Terrazzo & natural stone	✓	✓	✓	✓	✓
Quarry tiles	✓	✓	✓	✓	✓
Unglazed ceramic tiles	✓	✓	✓	✓	✓
Asphalt (flooring grade)	X	✓	✓	✓	✓
Anhydrite screed (prepared)	✓	✓	✓	✓	✓
Timber floors	X	X	X	✓*	✓**
Underfloor heating	X	✓	✓	✓	✓
<b>Tested to:</b>					
EN 13872:2004 - shrinkage	✓	✓	✓	✓	✓
EN 13892:2002 - compressive strength	✓	✓	✓	✓	✓
EN 12706:2000 - flow	✓	✓	✓	✓	✓
EN 13408:2002 - bond strength	✓	✓	✓	✓	✓

\* For tongue & groove flooring and 18mm single layer plywood use with BAL 4x4mm Fibreglass Mesh (1x10m roll)

\*\* Contact BAL Technical Advisory Service 0845 600 1222

Note: Refer to Technical Data Sheets for specific product usage



# NEW from **BAL**

## micromax grouts and sealants

**Fast drying, versatile floor and wall grouts and sealants in 9 co-ordinating colours.**

### key features grout

- Sets in only 2 hours
- Efflorescence-free/ water-repellent
- Superb finish
- Suitable for under-tile heating and plywood overlay floors
- Water/frost resistant

### microban antimicrobial protection

- Helps prevent growth of black mould
- Added hygiene protection

### coverage

- **2.5kg Grout**  
8.9m<sup>2</sup> with 300x300x9mm tiles and 3mm joints
- **5kg Grout**  
17.7m<sup>2</sup> with 300x300x9mm tiles and 3mm joints
- **310ml Sealant**  
12.0m<sup>2</sup> with 200x200x9mm tiles and 3mm joints
- **310ml Sealant**  
8.8m for 6x6mm bead

### colours

- White
- Manilla
- Champagne
- Pebble
- Chocolate
- Cocoa
- Gunmetal
- Smoke
- Ebony



## ctf4 adhesive

**PorcelBond Plus makes this new white adhesive perfect for large-format porcelain wall tiles.**

### key features

- Water/frost-resistant
- Non-slip
- Slow setting
- 5hrs pot time

### coverage

- 20kg at 3mm thickness typically covers:
- For dry wall areas: 8.0m<sup>2</sup>
  - For wet wall areas: 6.6m<sup>2</sup>
  - For floors: 5.0m<sup>2</sup>

